

Attorney's Docket No.: 14083-004002

Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Previously Presented)      An assembly comprising:  
an actuator with a longitudinal axis having a fixed end,  
and a free end configured to translate in three orthogonal  
directions with respect to said fixed end;  
a multiple bar linkage having first and second links  
mutually constrained to translate with respect to each other,  
and wherein said first link is fixed to a reference  
structure and said second link is constrained to translate in a  
direction generally parallel to the longitudinal axis of said  
actuator; and  
a coupling having first and second ends, said first end  
being fixed to said actuator proximate to a free end of said  
coupling, and said second end being fixed to said second link,  
the coupling adapted to transmit displacement in a direction  
substantially parallel to the longitudinal axis of said  
actuator.

2. (Original)      The assembly of claim 1, wherein said  
actuator has a z-axis translating section, and an x and y-axis  
translating section disposed between said fixed end and said z-  
axis translating section.

Attorney's Docket No.:14083-004002

3. (Previously Presented) The assembly of claim 2, wherein said reference structure is mechanically independent from translation of said z-axis translating section, but mechanically responsive to said x and y-axis translating section.

4. (Previously Presented) The assembly of claim 3, wherein said reference structure is fixed to said multiple bar linkage to deflect said multiple bar linkage in X and Y directions in response to X and Y deflections of said x and y-axis translating section.

5. (Currently Amended) The assembly of claim 4, wherein said ~~multi-bar~~ multiple bar linkage further includes a first mirror fixed to at least one of said links of the ~~multiple-bar~~ multiple bar linkage, and a second mirror fixed to another of said links of said ~~multi-bar~~ multiple bar linkage.

6. (Original) The assembly of claim 5, wherein the assembly is adapted to be supported in a chassis, and further wherein said first mirror is disposed in the path of a light beam from a light source mounted on said chassis and is disposed to reflect the light toward said second mirror.

Attorney's Docket No.:14083-004002

7. (Previously Presented) The assembly of claim 1, wherein the assembly is in a scanning probe microscope.

8. (Original) The assembly of claim 1, wherein said actuator is a piezoelectric actuator.

9-13 (Cancelled)

14. (Currently Amended) The assembly of claim 1, wherein said actuator has a z-axis translating section, and an x and y-axis translating section disposed between said fixed end and said z-axis translating section,

wherein said ~~measuring device~~ multiple bar linkage includes a movable bar assembly coupled to the actuator and to a reference structure, said bar assembly having a reflecting surface that is adapted to deflect ~~said a beam to create a deflected beam~~, and wherein said bar assembly is responsive to movement of the actuator so as to change the direction of said deflected beam.

15. (Currently Amended) The ~~apparatus~~ assembly of claim 14, wherein said bar assembly includes a first link having a first end attached to the actuator and a second end, and a

Attorney's Docket No.: 14083-004002

second link defining said reflecting surface and having a first opposed end rotatably attached to said second end and a second opposed end rotatably attached to said reference structure.

16. (Currently Amended) The ~~apparatus~~ assembly of claim 14, wherein said reference structure is tubular and generally surrounds the actuator.

17. (Currently Amended) The ~~apparatus~~ assembly of claim 16, wherein said reference structure is configured to allow said light beam and said deflected beam to pass therethrough.

18. (Currently Amended) The ~~apparatus~~ assembly of claim 17, wherein said reference structure has an inner surface.

19. (Currently Amended) The ~~apparatus~~ assembly of claim 18, further including a reflective surface fixed to said inner surface to steer said beam toward said reflecting surface.

20. (Currently Amended) The ~~apparatus~~ assembly of claim 14, wherein said bar assembly includes a link having opposed ends, a first opposed end rotatably attached to the actuator and a second opposed end rotatably attached to said reference

Attorney's Docket No.: 14083-004002

structure.

21. (Currently Amended) The ~~apparatus~~ assembly of claim 14, wherein said bar assembly comprises a four bar linkage including first and second reflecting surfaces, said surfaces disposed to reflect light such that the incoming and outgoing beams are generally parallel.

22-25. (Cancelled)

26. (Original) A method for measuring movement of an actuator in a metrology apparatus, the method comprising:  
providing a movable bar assembly coupled to the actuator and to a reference structure; and

measuring, in response to movement of the actuator, movement of said movable bar assembly, wherein movement of said movable bar assembly is indicative of movement of the actuator.

27. (Currently Amended) The method of claim 26, wherein said movable bar assembly includes a first link having a first end attached to the actuator and a second end, and a second link defining said reflecting surface and having a first opposed end rotatably attached to said second end and a second opposed end rotatably attached to said reference structure.

Attorney's Docket No.: 14083-004002

28. (Cancelled)

29. (Previously Presented) An apparatus for measuring movement of an actuator, the apparatus comprising:

an optical measuring device including a source of electromagnetic radiation that generates a beam;

a sensor that detects a position of said beam; and

wherein, in response to movement of the actuator, said optical measuring device changes the position of said beam further including a reference frame wherein said reference frame has a longitudinal axis that is generally co-linear with the longitudinal axis of the actuator.

30. (Original) The apparatus of claim 29, wherein said measuring device includes a movable bar assembly that is attached to said actuator at a first end of said bar assembly, and is attached to said reference frame at a second end of said bar assembly, and wherein said bar assembly defines a reflecting surface that reflects said beam towards said sensor.

31. (Original) The apparatus of claim 30, wherein said reference frame includes an inner surface and said measuring device further comprises a reflective surface fixed to said

Attorney's Docket No.:14083-004002

inner surface that steers said beam towards said reflecting surface, said reflecting surface deflecting said beam towards said sensor.

32. (Original) The apparatus of claim 30, wherein said reference frame is configured to allow said beam and said deflected beam to pass therethrough.

33-37. (Cancelled)